



Note:

- Material: Housing-polycarbonate, clear Terminal-0.36[.014] thick phosphor bronze. Thick gold in localized gold plate. Area, Gold Flash over the remainder. Over 2.54mm[.000100] thick nickel underplate.

Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length
AT-S-26-4/4/S-5	A	1,525±20(5ft)	Silver	1,525-1,535mm
AT-S-26-4/4/S-7	B	2,135±30(7ft)	Silver	2,135-2,145mm
AT-S-26-4/4/S-10	C	3,050±60(10ft)	Silver	3,050-3,060mm
AT-S-26-4/4/S-12	D	3,660±60(12ft)	Silver	3,660-3,670mm
AT-S-26-4/4/S-14	E	4,270±60(14ft)	Silver	4,270-4,280mm
AT-S-26-4/4/S-25	F	7,625±100(25ft)	Silver	7,625-7,635mm
AT-S-26-4/4/S-50	G	15,250±150(50ft)	Silver	15,250-15,260mm

P1		P2
1	BLACK	4
2	RED	3
3	GREEN	2
4	YELLOW	1

Unit: mm



Scale	Free					Date	Name
TOLERANCE						Drawn	03.07.13 Wilson
X.	±X					Approved	03.07.13 Groll
X.X	±X						
X.XX	±X						
DIM	TOL						
X.°	±X°						
X.X°	±X°						
Angle	TOL	Id.	Modification	Date	Name	 1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283 Toll Free: 1-877-277-6266 • Email: info@assmann.us	

Title
Modular cable - Straight 4P4C 50µm, 26AWG, Silver, 5-50 feet
ASSMANN WSW-No. AT-S-26-4/4/S-xx
Drawing-No.
Replace
Sheet 1/1

A
B
C
D
E
F
G
H